



HIGHEST PERFORMANCE AT THE LEAST COST

WONDER MUD®

Multi-purpose drilling fluid for the foundation and the drilling industries.
Ideal lubrication slurry for casings and microtunneling.

INFORMATION SHEET

Composition	Acrylamide/sodium acrylate copolymer emulsion.
Polymer content	33%
Physical properties	White liquid. Slight odor. Neutral pH. Solubility in water : 5% @ 20°C. Specific gravity : 1
Proportioning	5 gallons of WONDERMUD® will yield 3,000 to 5,000 gallons of mud depending on water quality and viscosity required.
Toxicity	None.
Impurities	None.
Packaging	5 gal. pails containing 42 lbs of product or 55 gal. drums
Storage and Handling	Keep containers sealed when not in use. Keep floor area clean: very slippery product when wet.
Spillage	Contain spill with absorbing materials. Dispose in solid waste container. Clean spill area with chlorinated water.
Breakdown	Mud viscosity may be broken with strong oxydizers such as chlorine or a mild acid preferably in dry form.
Precautions	Do not expose to open flame. Product contains petroleum distillate. Flash Point is above 145° F. Boiling Point is 210° F. Self-ignition temperature is over 700° F.
Fire	Use Carbon Dioxide (CO ₂) foam extinguishers.